

Vipac Engineers & Scientists Ltd.
279 Normanby Rd, Port Melbourne, VIC 3207, Australia
Private Bag 16, Port Melbourne, VIC 3207
w. www.vipac.com.au | A.B.N. 33 005 453 627 | A.C.N. 005 453 627

# **ASLI Mechanical Sdn Bhd**

# Airflow and Acoustic Research and Development Study of one (1) Diffuser Face Size: 1200mm x 1-slot x 50mm



Report No. 30S-15-0077-TRP-390193-0

Vipac Engineers & Scientists Ltd Melbourne, Australia November 2015







# **DOCUMENT CONTROL FORM**

Airflow and Acoustic Research and Development Study of one (1) Diffuser (Face Size: 1200mm x 1-slot x 50mm)

DOCUMENT NO:		REPORT CODE:			
30S-15-0077-TRP	-390193-0	TRP			
PREPARED FOR:		PREPARED BY:			
ASLI Mechanical Sdn Bhd		Vipac Engineers & Scientists Ltd.,			
Lot 20, Masalam Industrial Estate		Victorian Technology Centre,			
Rawang, Selangor Darul Ehsan		275 Normanby Road,			
Rawang, 48000, Malaysia		Port Melbourne VIC. 3207			
		AUSTRALIA			
Contact Person:	Boon Thiam Yap				
Phone:	+603 6092 6652	Phone: (613) 9647-9755			
Fax:	+603 6092 1035	Fax: (613) 9646-4370			

PREPARED AND AUTHORISED BY:	€ è			
	Zarko Drinic	Date: 17 <sup>th</sup> November 2015		
	Authorised Signatory			
REVIEWED BY:	166			
	Greg King	Date: 17 <sup>th</sup> November 2015		
	Operation Manager			
REVISION HISTORY:				
Issue No.	Date Issued	Reason/Comments		
0	November 2015	Original Data		
DISTRIBUTION:				
This is Copy No.	Issue No.	Location		
1	0	Client		
2	0	Vipac (Job Control)		
KEY WORDS:	Air Flow Rate, Pressure, Noise, Diffuser			

NOTE: This is a controlled document within the document control system. If revised, it must be marked SUPERSEDED and returned to the Vipac QA Representative.

This document contains commercial, conceptual and engineering information which is proprietary to Vipac Engineers & Scientists Ltd. We specifically state that inclusion of this information does not grant the Client any license to use the information without Vipac's written permission. We further require that the information not be divulged to a third party without our written consent.

Ref: 30S-15-0077-TRP-390193-0

November 2015



NATA Accredited Laboratory Number: 676 Accredited for compliance with ISO / IEC 17025. The results of the tests, calibrations and/or measurements included in this document are traceable to Australian / national standards.



# **TABLE OF CONTENTS**

DOO	CUMENT CONTROL FORM	
	INTRODUCTION	
2.0	TEST SPECIMEN	4
3.0	TEST CONDITIONS AND APPLICABLE STANDARDS	5
4.0	TEST SET UP AND SPECIFICATION	6
5.0	INSTRUMENTATION	8
6.0	ORDERS OF ACCURACY	8
7.0	RESULTS	9
	COUSTIC AND AIRFLOW PERFORMANCE TESTS	
- 1	ECEND	10





### 1.0 INTRODUCTION

This report presents the results of airflow and acoustic tests carried out on one (1) Diffuser, supplied by "ASLI Mechanical Sdn Bhd", as described below.


### 2.0 TEST SPECIMEN

The unit under test is detailed in Table 1 below.

**Table 1: Units Under Test** 

#	Product Name	Slot Length (mm)	Slot Width (mm)		
1	One (1) Slot Jet Ceiling Diffuser	1200	50		
	Model: SJS-A				

Photographs of the Test Unit are shown in Figure 1 below.



1d) Diffuser Front View

Figure 1: One (1) Slot Jet Ceiling Diffuser (Model: SJS-A)

Ref: 30S-15-0077-TRP-390193-0

NATA Ac Laborator

November 2015

NATA Accredited Laboratory Number: 676



### 3.0 TEST CONDITIONS AND APPLICABLE STANDARDS

### 3.1 TEST CONDITIONS

The unit under (acoustic) tests was supplied with ambient temperature air at the following conditions:

Air Temperature	17 °C	± 3 °C
Barometric Pressure	101 kPa	± 2 kPa
Relative Humidity	55	<u>+</u> 10 %

### 3.2 APPLICABLE STANDARDS

The unit was tested at a range of flow conditions, as shown on the Test Certificate.

The test set up was in general accordance with ANSI/ASHRAE 70-2006 Standard. Measurements were taken in general accordance with the following standards:

### **ACOUSTICS**

AS 1217.2-1985 Acoustics – Determination of sound power levels of noise sources Part 2: Precision methods for broad-band sources in reverberation rooms.

ISO 3741-1999 Acoustics – Determination of sound power levels of noise sources using sound pressure. Precision methods for reverberation rooms.

### <u>AIRFLOW</u>

ANSI/ASHRAE 70-2006 – Method of Testing the performance of Air Outlets and Air Inlets

### **THROW & STATIC PRESSURE DROP**

ANSI/ASHRAE 70-2006 – Method of Testing the performance of Air Outlets and Air Inlets



### 4.0 TEST SET UP AND SPECIFICATION

Vipac's Reverberation Test Room has a volume of 170m<sup>3</sup> has been qualified in accordance with the procedures in AS 1217.2-1985 (ISO 3741–1999) for determination of sound power in octave bands with Centre Frequencies from 125 Hz to 8000 Hz.

The unit under test was set up in the Air Distribution (Reverberation) Test Chamber and connected to a quiet air supply.

Following calibration checks, sound pressure levels were measured and converted to sound power levels using the comparison method of AS 1217.2 - 1985 (ie. using a reference sound source of known Sound Power to determine room correction).

Airflow rates were measured using  $\emptyset$  150 mm orifice plate. Static pressure drop was recorded using a (Static Pressure) probe and a digital manometer. Throw was measured using a hotwire type anemometer. Figure 2 shows diffuser slot position for horizontal throw measurements. Figure 3 shows the test setup.



Figure 2: Horizontal Throw Setup




Figure 3: Test Set-up (Air Distribution Laboratory)

Australian / national standards.



# 5.0 INSTRUMENTATION


INSTRUMENT	MAKE & MODEL	CALIBRATION		SERIAL NO.
		BY	DATE	
Sound Level Meter	ONO SOKKI LA-5570	Vipac	March 2015	64401234
Acoustic Calibrator	B&K 4230	Vipac	March 2015	860700
Manometers	EMA 200 PVM 610	GTS GTS	July 2015 July 2015	B/C: 000013792 PVM610718009
Orifice Plates	Ø 150	Vipac	May 2013	-
Airflow Anemometer	TSI 9545	UKAS	July 2015	9545A0813010


# 6.0 ORDERS OF ACCURACY

Sound Pressure Level:	Octave Band Centre	Standard Deviation (1)
	Frequency (Hz)	(dB)
	125	<u>+</u> 3.0
	250	<u>+</u> 2.0
	500 to 4000	<u>+</u> 1.5
	8000	<u>+</u> 3.0

<u>Pressure Drop:</u> ± 5% or 1 Pa whichever is greater

<u>Airflow:</u> ± 5% or 10 L/s whichever is greater







# 7.0 RESULTS

The results obtained are shown in the attached Test Certificate.

Report Prepared by: VIPAC ENGINEERS AND SCIENTISTS LTD.

**GREG KING** 

**OPERATION MANAGER** 

ZARKO DRINIC

**AUTHORISED SIGNATORY** 





# TEST CERTIFICATE (J/N: 30S-15-0077)

### **ACOUSTIC AND AIRFLOW PERFORMANCE TESTS**

SUPPLIED BY: ASLI MECHANICAL SDN BHD

TESTED BY: VIPAC ENGINEERS & SCIENTISTS LTD

TEST DATE: November 2015 EXPIRY DATE: November 2018

CLIENT: ASLI MECHANICAL SDN BHD

UNIT: One (1) Slot Jot Ceiling Diffuser (Model: SJS-A)

SIZE: 1200 mm x 1-slot x 50mm (Diffuser Face)

308mm x 129mm (Plenum Neck)

**HORIZONTAL THROW** 

TEST CONDITIONS				SOUND POWER LEVEL, dB re 1E-12 W OCTAVE BAND CENTRE FREQUENCY (Hz)						
Qs (L/s)	Ps (Pa)	T (m)	NC	125	250	500	1000	2000	4000	8000
128	27	2	22	43.0	44.5	37.6	32.4	25.5	<18.4	<17.0
152	39	3	27	47.4	48.4	41.7	36.8	30.5	24.6	<18.4
184	56	4	33	52.1	53.3	47.0	42.5	37.4	32.2	24.1
218	77	6	38	57.1	57.9	51.9	47.4	42.8	38.3	30.8
248	100	>7	43	60.0	61.8	55.5	51.0	47.1	43.0	36.3

### **LEGEND**

Qs - Primary Air Flow Rate (L/s)

Ps - Supply Static Pressure (Pa)

T - Horizontal Throw in meters to a terminal velocity of 0.25 m/s (m)

Insufficient margin above background noise to allow accurate determination

> - Length of throw greater than that able to be measured

NC - Noise Criterion based upon room absorption of 10 dB

GREG KING

OPERATION MANAGER

ZARKO DRINIC

**AUTHORISED SIGNATORY** 

November 2015

Ref: 30S-15-0077-TRP-390193-0




NATA Accredited Laboratory Number: 676 Accredited for compliance with ISO / IEC 17025. The results of the tests, calibrations and/or measurements included in this document are traceable to Australian / national standards.



# Appendix A

Drawing supplied by "ASLI Mechanical Sdn Bhd"





Ref: 30S-15-0077-TRP-390193-0



NATA Accredited Laboratory Number: 676 November 2015